## NSN 9320-00-641-7087

Cellular Rubber Sheet - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/9320-00-641-7087   |
|---|
| Fabrication Method:   |
| Cellular, unexploded  |
| Nonmetallic Hardness Rating:                                    |
| 45.0 shore durometer a and 55.0 shore durometer a               |
| Min. Tensile Strength (psi):                                    |
| 1200 pounds per square inch                                     |
| Width:  |
| Between 36.000 inches and 36.750 inches                         |
| Tempurature Rating:   |
| -31.0 degrees celsius   |
| Thickness:  |
| Between 0.031 inches and 0.093 inches                           |
| Length:   |
| Between 36.000 inches and 36.750 inches                         |
| Surface Condition:  |
| Smooth both sides   |
| Environmental Protection:                                       |
| Fire resistant and low temperature and oil resistant            |
| Material:   |
| Rubber, cellular, mil-r-6130, type 2, grade a, condition medium |
| Material:   |
| Rubber chloroprene class cr                                     |
| Specification Or Standard:                                      |
| Medium condition and a grade and ii type                        |
| Departure From Cited Designator:                                |
| As modified by nonmetallic hardness rating and tensile strength |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
|   |

Mil-std (military Standard): Mil-r-6130 spec.