

View Online at <https://aerobasegroup.com/nsn/9320-00-684-3338>

**Cross Sectional Shape:**

Rectangular

**Fabrication Method:**

Cellular, unexploded

**Nonmetallic Hardness Rating:**

35.0 shore durometer a

**Min. Tensile Strength (psi):**

15 pounds per square inch

**Temperature Rating:**

-55.0 degrees celsius and 100.0 degrees celsius

**Length:**

10.500 inches

**Surface Condition:**

Smooth both sides

**Cross-sectional Height:**

0.625 inches

**Cross-sectional Width:**

0.375 inches

**Environmental Protection:**

Alcohol resistant and sodium chloride and water resistant and non-oil resistant

**Material:**

Rubber, mil-std-670, type r, style e, grade re3lz or rubber, mil-std-670, type r, style e, grade re7lz

**Material:**

Rubber butadiene-styrene class sbr or rubber polyisoprene natural class nr or rubber butadiene-styrene class sbr or rubber polyisoprene natural class nr

**Material Specification:**

Mil-std-670, type r, style e, grade re3lz military specification 1st material response and mil-std-670, type r, style e, grade re7lz military specification 2nd material response

**Specification Or Standard:**

Re3lz grade or re7lz grade

**Departure From Cited Document:**

As modified by hardness rating, tensile strength, and environmental protection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A26800

**Mil-std (military Standard):**

Mil-std-670 spec.