## NSN 9320-01-053-0639

Rubber Strip - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9320-01-053-0639

| Cross Sectional Shape:  |
|---|
| Square  |
| Fabrication Method:   |
| Extruded  |
| Nonmetallic Hardness Rating:  |
| 40.0 shore durometer a and 60.0 shore durometer a                           |
| Min. Tensile Strength (psi):  |
| 700 pounds per square inch  |
| Length:   |
| 18.000 inches   |
| Surface Condition:  |
| Smooth both sides   |
| Cross-sectional Height:   |
| Between 0.078 inches and 0.113 inches                                       |
| Cross-sectional Width:  |
| Between 0.100 inches and 0.150 inches                                       |
| Environmental Protection:   |
| High temperature  |
| Material:   |
| Rubber, silicone, zz-r-765, class 2b, grade 50                              |
| Material:   |
| Rubber silicone class q   |
| Material Specification:   |
| Zz-r-765, class 2b, grade 50 federal specification single material response |
| Specification Data:   |
| 90536-7957018 professional/industrial association standard                  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| -   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A26800  |
|   |
|   |