

View Online at <https://aerobasegroup.com/nsn/9320-01-541-5666>

**Nonmetallic Hardness Rating:**

4.9 shore durometer a

**Min. Tensile Strength (psi):**

Any acceptable

**Width:**

9.000 inches

**Thickness:**

0.200 inches

**Length:**

9.000 inches

**Surface Condition:**

Smooth both sides

**Strengthening Feature Material:**

Ceramic particles

**Environmental Protection:**

Compression and heat resistant

**Strengthening Feature:**

Internally molded-in reinforcement

**End Application:**

Tact aircrew combat training system; an/gsq-t103 c

**Product Name:**

Therm-a-gap highly conformable, thermally conductive gap filler, ceramic-filled-silicone elastomer on 5 military aluminum carrier

**Special Features:**

Flexible, elastic nature allows item to blanket highly uneven surfaces, drawing away and transferring heat from components such as microprocessors, video chips and power devices; thermal impedance: 2.86 degrees c-square inch/w at 10 psi (modified astm d5470); thermal conductivity: 1.6 w/m-k at 10 psi (modified astm d5470)

**Color:**

Gray, light both sides

**Material:**

Silicone rubber

**Material:**

Rubber silicone class q

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A26800