NSN 9320-01-541-5666

Solid Rubber Sheet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9320-01-541-5666

Nammatallia Handmaga Datin m
Nonmetallic Hardness Rating:
4.9 shore durometer a
Min. Tensile Strength (psi):
Any acceptable
Width:
9.000 inches
Thickness:
0.200 inches
Length:
9.000 inches
Surface Condition:
Smooth both sides
Strengthening Feature Material:
Ceramic particles
Environmental Protection:
Compression and heat resistant
Strengthening Feature:
Internally molded-in reinforcement
End Application:
Tact aircrew combat training system; an/gsq-t103 c
Product Name:
Therm-a-gap highly conformable, thermally conductive gap filler, ceramic-filled-silicone elastomer on 5 military aluminum carrier
Special Features:
Flexible, elastic nature allows item to blanket highly uneven surfaces, drawing away and transfering heat from components such as
microprocessors, video chips and power devices; thermal impedance: 2.86 degrees c-square inch/w at 10 psi (modified astm d5470);
thermal conductivity: 1.6 w/m-k at 10 psi (modified astm d5470)
Color:
Gray, light both sides
Material:
Silicone rubber
Material:
Rubber silicone class q
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A26800