

View Online at <https://aerobasegroup.com/nsn/9330-01-501-6206>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

16.560 inches

**Thickness:**

4.000 inches

**Length:**

23.400 inches

**End Application:**

Aircraft thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with 3 cutouts on right/short edge: 1.25x1.3, 2 inches from bottom, 1.25x1.0, 6.2 inches from bottom, and 1.25x1.56, 1.04 inches from top; has a 4.5x2.0 inch groove cut out on far side, starting 8.8 inches from bottom and extending from right edge; a 2.0x2.0 groove along bottom edge of far side and a 2.0dx1.56w groove on far side along top edge; marked with words "up" and "aft" on far side near top edge and with part number on far side in bottom groove near un-notched edge

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmsr-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T258-d