

View Online at <https://aerobasegroup.com/nsn/9330-01-501-6206>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.560 inches

Thickness:

4.000 inches

Length:

23.400 inches

End Application:

Aircraft thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 3 cutouts on right/short edge: 1.25x1.3, 2 inches from bottom, 1.25x1.0, 6.2 inches from bottom, and 1.25x1.56, 1.04 inches from top; has a 4.5x2.0 inch groove cut out on far side, starting 8.8 inches from bottom and extending from right edge; a 2.0x2.0 groove along bottom edge of far side and a 2.0dx1.56w groove on far side along top edge; marked with words "up" and "aft" on far side near top edge and with part number on far side in bottom groove near un-notched edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmsr-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T258-d