

View Online at <https://aerobasegroup.com/nsn/9330-01-501-6394>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.750 inches

Thickness:

2.500 inches

Length:

23.400 inches

End Application:

Aircraft thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Urectangularwith 3 cutouts on right short edge: 1.25wx1.18h, 2.12 in. Up from bottom, 1.25wx1.00h, 5.96 up from bottom and 1.25wx1.76h, 13.96 up from bottom; a groove 1.86dx2.03w on far side top lengthwise edge; a groove1.7dx2.12w on far side bottom lengthwise edge; a trapezoidal cutout on near side below top groove, deeper on right side; markings on far side; "up"p and"aft" on 2 lines near top groove and un-notched edge and partnumber on far side in lower groove near notched edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmsr-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d