

View Online at <https://aerobasegroup.com/nsn/9330-01-501-6438>

Fire Retarding Characteristic:

Not fire retarding

Width:

18.400 inches

Thickness:

4.000 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with cutouts on right/short edge: 1.25wx1.52h, 2.0 inches from bottom and 1.25wx1.76h, 14.4 inches from bottom; a circular hole with 3.50 in. Diam cut thru, centered 11.56 up from bottom and 10.31 from left edge; on near side: a groove 2.52wx0.60d along top edge and a groove 2.00wx0.56d along lower edge; on far side: a groove 1.76wx0.72d along top edge and a groove 2.36wx0.86d along bottom edge, markings "up" and "aft" on 2 lines below top groove and near un-notched edge, part number in lower groove near un-notched edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d