

View Online at <https://aerobasegroup.com/nsn/9330-01-501-6443>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.000 inches

Thickness:

2.500 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Vrectangular with cutouts on right/short edge: 1.25wx1.18h, 1.88 inches from bottom and 1.25 wx1.32h, 14.54 from bottom; a hole with 3.50 inch diameter cut thru, centered 11.06 from bottom and 10.32 from un-notched edge; near side has a groove 0.56dx1.88w along bottom edge and a groove 0.56dx2.00w along top edge; on far side: markings "up" and "aft" on 2 lined near top groove and between circular hole and un-notched edge, and part number marked near lower edge and near notched edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d