## NSN 9330-01-501-6449

Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-501-6449

| Fire Retarding Characteristic:   |          |
|--|----------|
| Not fire retarding   |          |
| Width:   |          |
| 17.440 inches  |          |
| Thickness:   |          |
| 4.000 inches   |          |
| Length:  |          |
| 19.400 inches  |          |
| End Application:   |          |
| Aircraft, thunderbolt ii, a-10   |          |
| Surface Condition:   |          |
| Rough  |          |
| Density Rating:  |          |
| 1.2 pounds per cubic foot  |          |
| Compression Strength At 25 Pct Deflection:   |          |
| 0.35 pounds per square inch  |          |
| Product Name:  |          |
| Filler foam  |          |
| Special Features:  |          |
| Rectangular; far side bottom/long edge is tapered down to 0.36 inch from bottom edge; hole 3.50 inch in diameter cut through is    | centered |
| 10.68 inch up from bottom and 10.28 over from left edge; far side is marked with "up" and "aft" on 2 lines on upper right quadrant | and with |
| part number on lower right quadrant  |          |
| Material:  |          |
| Plastic, polyurethane  |          |
| Material:  |          |
| Plastic polyurethane   |          |
| Supplementary Features:  |          |
| Material to be reticulated foam per sm-alc specification ms-mmrs-87-100  |          |
| Shelf Life:  |          |
| N/a  |          |
| Unit Of Measure:   |          |
|  |          |
| Demilitarization:  |          |
| No   |          |
| Fiig:  |          |
| T258-d   |          |