

View Online at <https://aerobasegroup.com/nsn/9330-01-501-6456>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.200 inches

Thickness:

4.000 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with cutouts on right/short edge: 1.25w x1.00h, 3.28 inches from bottom edge & 1.25wx1.00h, 14.40 from bottom edge; a hole 4.0 inches in diam, cut thru, centered 10.22 up from bottom and 13.09 over from right edge; on near side: a groove 2.00dx4.0w along right side and a h-shaped groove 1.76d centered crosswise around the circular hole with legs 1.12w and cross bar extending 0.50 inch beyond hole on both sides; far side has markings "up" and "aft" on 2 lines near top edge and near un-notched edge and part number near top and near notched edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d