

View Online at <https://aerobasegroup.com/nsn/9330-01-501-6485>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.400 inches

Thickness:

4.000 inches

Length:

20.940 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Irregularly shaped; left edge has wing-shaped piece extending 9.4 inches up from bottom and 7.80 to left of left edge at top of wing and 2.0 to left at bottom of wing; right edge has a cutout 1.26wx1.56h, 2.24 from top edge and a cutout 4.64hx4.70w, 1.56 up from bottom with bottom right corner of cut out section rounded to radius of 1.00 inch; near side has markings "up" and "aft" in 2 lines near top right edge and part number near top left edge and a lengthwise groove 1.28wx2.24d starting 1.00 inch down from top edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d