

View Online at <https://aerobasegroup.com/nsn/9330-01-501-6631>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.360 inches

Thickness:

2.500 inches

Length:

20.890 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/shorter edge: 1.25wx1.00h, 2.96 inches from bottom and 1.25wx1.00h, 13.80 from bottom; a cutout on bottom edge, 1.16hx16.73w, 1.16from left edge; a rectangular hole, 10.59wx2.00h, cut thru, 8.90 from bottom and 7.30 from left edge; a groove 1.00hx7.30wx1.00d on near side horizontally to left of hole and one 2.0hx3.00wx1.00d on far side horizontally to right of hole; far side has groove 1.15wx1.0d along left crosswise edge; near side is marked with "up" and "fwd" in upper center area and with part number in lower center area

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d