NSN 9330-01-501-7093

Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-501-7093

Not fire retarding Width: 15.400 inches Thickness: 2.500 inches Length: 20.940 inches End Application: Aircraft, thunderbott ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on togedge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Material: Plastic polyurethane Material: Via Unit Of Measure: - Demilitarization: No	Fire Retarding Characteristic:
15.400 inches Thickness: 2.500 inches Length: 20.940 inches End Application: Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from light edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on top edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: Na Unit Of Measure: Demilitarization:	Not fire retarding
Thickness: 2.500 inches Length: 20.940 inches End Application: Aircraft, thunderbott ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on top edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Width:
2.500 inches Length: 20.940 inches End Application: Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on togedge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	15.400 inches
Length: 20.940 inches End Application: Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on top edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit of Measure: Demilitarization:	Thickness:
20,940 inches End Application: Aircraft, thunderbott ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on top edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	2.500 inches
End Application: Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on top edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Length:
Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on togedge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	20.940 inches
Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on top edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	End Application:
Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on toge edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Aircraft, thunderbolt ii, a-10
Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on togedge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Surface Condition:
1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on togedge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Rough
Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on togedge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Density Rating:
0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on togedge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	1.2 pounds per cubic foot
Product Name: Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on togedge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Compression Strength At 25 Pct Deflection:
Filler foam Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on togedge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	0.35 pounds per square inch
Special Features: Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on togedge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Product Name:
Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and 1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on top edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Filler foam
1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom; near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on top edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Special Features:
near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40 inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on top edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Rectangular with 3 cutouts on right/short edge: 1.12wx1.44h, 1.44 inch from bottom edge, 1.12wx1.06h, 7.50 from bottom and
inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on top edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	1.12wx1.40h, 12.04 from bottom; a circle with diameter of 2.50 inches is cut thru, centered 3.50 from right edge and 5.20 from bottom;
edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	near side has an arc of a circle with radius of 7.75 in. Cut out from 5.90 inches from left edge to 13.60 from left edge with a length of 6.40
Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	inches and has markings "up" and "aft" on 2 lines near upper left corner and part number near bottom left edge; far side has taper on top
Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	edge of 0.64 inch and has 2 crosswise grooves 1.10wx1.30d, 6.86 and 13.60 inches from notched edge
Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Material:
Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Plastic, polyurethane
Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Material:
Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure: Demilitarization:	Plastic polyurethane
Shelf Life: N/a Unit Of Measure: Demilitarization:	Supplementary Features:
N/a Unit Of Measure: Demilitarization:	Material to be reticulated foam per sm-alc specification ms-mmrs-87-100
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No
Fiig:	Fiig:
T258-d	T258-d