

View Online at <https://aerobasegroup.com/nsn/9330-01-501-7125>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.000 inches

Thickness:

4.000 inches

Length:

20.940 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Nmost nearly rectangular in shape; right edge has cutout 1.25wx2.46h, 1.84 inches from bottom edge and cutout 4.70wx9.90 h, 4.30 from bottom; left edge has cutout 4.96wx5.00h from top corner; near side has groove 2.16wx2.28d along bottom edge and is marked with "up" and "aft" near center top and with part number centered above groove; far side has v-shaped cutout 11.00lx5.00w beginning on outer edges of upper portion of piece ending at depth of 1.75 inches in center

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d