

View Online at <https://aerobasegroup.com/nsn/9330-01-501-7164>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

15.680 inches

**Thickness:**

3.750 inches

**Length:**

17.680 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with 3 cutouts on right/long edge: 1.06wx1.10h, 2.30 from bottom, 3.30wx2, 00h, 6.00 from bottom, and 1.26wx1.58h, 13.80 from bottom; near side has a groove 2.30wx1.00d along bottom edge and one 2.30wx0.68d along top edge and is marked with "up" and "aft" on 2 lines near center top and with part number near upper left corner; far side is tapered -.50 along topedge and has top surface cutout starting from a depth of 2.50 on left/long side, over 4.33 inches to right, then slanting up to meet top edge 5.83 from left edge; right side has similar cutout, starting from depth of 2.50 on right side, 3.64 to left then slanting up to meet top edge 5.14 from right edge

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d