NSN 9330-01-501-7170

Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-501-7170

| Fire Retarding Characteristic: |
|---|
| Not fire retarding |
| Width: |
| 18.100 inches |
| Thickness: |
| 4.000 inches |
| Length: |
| 20.940 inches |
| End Application: |
| Aircraft, thunderbolt ii, a-10 |
| Surface Condition: |
| Rough |
| Density Rating: |
| 1.2 pounds per cubic foot |
| Compression Strength At 25 Pct Deflection: |
| 0.35 pounds per square inch |
| Product Name: |
| Filler foam |
| Special Features: |
| Oroughly rectangular: right/short edge has 2 cutouts: 1.26wx1.60h, 1.94 from bottom and 3.30wx9.80h, 6.00 from bottom and a cutout or |
| left edge, 5.50wx2.30h at top left corner; near side has groove 2.16wx0.94d along bottom edge and is marked |
| Material: |
| Plastic, polyurethane |
| Material: |
| Plastic polyurethane |
| Supplementary Features: |
| Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filig: |
| T258-d |
| |
| |