NSN 9330-01-501-7440

Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-501-7440

| Fire Retarding Characteristic: |
|---|
| Not fire retarding |
| Width: |
| 13.600 inches |
| Thickness: |
| 2.750 inches |
| Length: |
| 20.940 inches |
| End Application: |
| Aircraft, thunderbolt ii, a-10 |
| Surface Condition: |
| Rough |
| Density Rating: |
| 1.2 pounds per cubic foot |
| Compression Strength At 25 Pct Deflection: |
| 0.35 pounds per square inch |
| Product Name: |
| Filler foam |
| Special Features: |
| Rectangular with 2 cutouts on right/short side; 1.25wx1.40h, 2.20 from bottom edge and 1.25wx1.20h, 10.56 from bottom edge; near side |
| has 2 crosswise grooves 1.12wx1.12d, 5.92 inches from right edge and 6.10 from left edge, bottom is tapered 0.26; far side has markings |
| "up" and "fwd" on 2 lines near center top and part number near top and un-notched edge |
| Material: |
| Plastic, polyurethane |
| Material: |
| Plastic polyurethane |
| Supplementary Features: |
| Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T258-d |
| |
| |