

View Online at <https://aerobasegroup.com/nsn/9330-01-501-7448>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.380 inches

Thickness:

4.000 inches

Length:

20.940 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Roughly rectangular with rounded cutout, with radius of 2.5, extending 8.40 inches from right/short edge and one with radius of 2.05, extending 11.8 from left edge, a cutout 8.79wx1.16h, 5.75 from left along bottom edge; near side has rounded cutout lengthwise with 2.0 radius, 6.80 from bottom edge, bottom edge has lengthwise groove 2.20wx1.40d; far side has groove 2.20wx1.40h along top edge and has markings "up fwd" above rounded cutout and part number in top groove near opposite edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d