

View Online at <https://aerobasegroup.com/nsn/9330-01-501-7474>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.400 inches

Thickness:

2.500 inches

Length:

19.940 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Oughly rectangular with cutout 5.80wx11.90h from upper right courner and one 9.0wx6.4h with inner corners rounded to radius of 1.0, 1.20 up from bottom left corner; near surface has 7.50w lengthwise v-shaped cutout beginning 1.04 from bottom right edge, slanting downward to 0.50 from bottom surface (and rounded ther to 2.0 radius), 15.60 from left edge, then slanting back up to meet top surface 5.80 from left edge; far side has markings: "up" and "fwd" on 2 lines near top edge and part number to right of these words

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d