

View Online at <https://aerobasegroup.com/nsn/9330-01-501-7506>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.600 inches

Thickness:

2.500 inches

Length:

20.940 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

4rectangular with 2 cutouts from right/short edge: 4.20wx4.60h from bottom corner and 1.26wx1.40h, 2.20 from top; 2 cutouts from top edge: 2.20wx8.00h with bottom left corner rounded to 1.00 radius, 2.20 from left edge and 3.80wx5.75h, 3.20 from left edge; a 1.80wx3.00h cutout from bottom left corner; near side is tapered 0.30 on bottom edge and has markings: "up" and "aft" on 2 lines next to 1.26x1.40 notch and part number centered near bottom edge; far side has groove 2.20wx1.00d along top edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d