

View Online at <https://aerobasegroup.com/nsn/9330-01-501-7524>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.440 inches

Thickness:

4.000 inches

Length:

19.800 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: 3.60wx4.40h from bottom corner and 2.50wx3.84h from top corner; a cutout 5.70wx4.24h from top left corner; near side has 0.50wx0.88d groove along bottom edge and tapers to far side edge; far side has 2 lengthwise grooves, 1.16wx1.70d, 5.20 from right edge and 11.20 from right edge and one lengthwise groove 3.20wx2.12d along left edge; near side has 1.36wx0.88d groove 0.50 in from bottom edge and has markings: "up" and "aft" on 2 lines centered near top edge and part number near bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d