

View Online at <https://aerobasegroup.com/nsn/9330-01-501-9213>

Fire Retarding Characteristic:

Not fire retarding

Width:

14.600 inches

Thickness:

4.000 inches

Length:

20.890 inches

End Application:

Aircraft, thunderbolt ii, a-10; sheur bolt

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Qrectangular with 2 cutouts on right/short edge: 1.25wx2.30h, 2.70 from bottom and 1.25wx3.00h, 9.48 from bottom; left side has cutout 1.25wx5.50h, 3, 85 from botom; near side has semicircular lengthwise cutout with radius of 2.00 inches, centered 6.60 in from bottom and 0.50 from top surface, and a lengthwise groove 2.20wx1.40d along top edge and has markings: "up fwd" centered in top groove and part number near bottom center; far side is tapered 0.56 along bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d