

View Online at <https://aerobasegroup.com/nsn/9330-01-501-9215>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

15.400 inches

**Thickness:**

4.000 inches

**Length:**

19.640 inches

**End Application:**

Aircraft, thunderbolt ii, a-10; sheur bolt

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with cutout on bottom/long edge, 7.75wx1.16h, 5.75 from left edge and cutout on left edge, 1.25wx5.75l, 4.44 from bottom, and cutout from top edge, 3.00wx6.0h, with rounded bottom, 5.00 from left side; near side has lengthwise groove, 2.30wx1.25d along to edge, a rectangular cutout 2.00wx5.00lx1.00d, parallel to long edge, beginning 8.24 inch from botom on right side and had markings "up fwd" in center of top groove and part number near center bottomn; far side has lengthwise groove, 2.75wx1.75d along bottom edge and lengthwise semicircular cutout with radius of 2.00 inches centered 7.19 from bottom edge

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d