

View Online at <https://aerobasegroup.com/nsn/9330-01-501-9215>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.400 inches

Thickness:

4.000 inches

Length:

19.640 inches

End Application:

Aircraft, thunderbolt ii, a-10; sheur bolt

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with cutout on bottom/long edge, 7.75wx1.16h, 5.75 from left edge and cutout on left edge, 1.25wx5.75l, 4.44 from bottom, and cutout from top edge, 3.00wx6.0h, with rounded bottom, 5.00 from left side; near side has lengthwise groove, 2.30wx1.25d along to edge, a rectangular cutout 2.00wx5.00lx1.00d, parallel to long edge, beginning 8.24 inch from botom on right side and had markings "up fwd" in center of top groove and part number near center bottomn; far side has lengthwise groove, 2.75wx1.75d along bottom edge and lengthwise semicircular cutout with radius of 2.00 inches centered 7.19 from bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d