

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0559>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.660 inches

Thickness:

4.000 inches

Length:

20.890 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Yrectangular with cutouts on right/short edge: 1.26wx2.70h at bottom right corner and 1.26wx3.660h at top right corner; near side has crosswise groove, 1.26wx1.70d along right side and tapers 0.76 along to edge; far side has lengthwise grooves, 2.36wx1.60d along top edge and 2.50wx2.25d along bottom edge and a cutout 4.10wx3.66hx1.60d, 13.00 inches above bottom edge, along un-notched side edge and has marking "up aft" near top notched corner and part number centered above lower groove

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d