

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0576>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.760 inches

Thickness:

2.500 inches

Length:

20.890 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with a cutout on bottom left corner, 1.50wx2.40h and a cutout on bottom right corner, 1.25wx9.05h; near side is tapered 0.30 at top edge and has crosswise groove: 1.50wx1.50d along left edge; far side has lengthwise groove: 2.40wx0.76d along bottom edge and markings "up" & "aft" on 2 lines near upper right corner (far side up) and part number centered above bottom groove; there is a cutout near the center: a circle with radius of 3.00 centered 10.80 above bottom edge and intersecting near surface 16.50 inches from left edge and intersecting far surface 10.00 from left edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d