

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0580>

Fire Retarding Characteristic:

Not fire retarding

Width:

18.180 inches

Thickness:

4.000 inches

Length:

20.890 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with cutout 1.00wx3.00h at bottom left corner, 2 cutouts on right/short edge: 1.25wx1.25h, 2.26 and 14.40 inches from bottom edge; near side is tapered 0.27 along top edge and has 2 grooves: 2.98wx0.84d along top edge and 2.26wx0.64d along bottom edge and has cutout, 8.60wx3.80hx3.40d, 8.65 up from right edge; far side has markings "up aft" in top groove near un-notched edge and part number above groove, near same edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d