

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0580>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

18.180 inches

**Thickness:**

4.000 inches

**Length:**

20.890 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with cutout 1.00wx3.00h at bottom left corner, 2 cutouts on right/short edge: 1.25wx1.25h, 2.26 and 14.40 inches from bottom edge; near side is tapered 0.27 along top edge and has 2 grooves: 2.98wx0.84d along top edge and 2.26wx0.64d along bottom edge and has cutout, 8.60wx3.80hx3.40d, 8.65 up from right edge; far side has markings "up aft" in top groove near un-notched edge and part number above groove, near same edge

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T258-d