

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0614>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.780 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

8rectangular with cutouts on right/short edge: 1.26wx1.00h, 1.94 and 12.64 inches from bottom and cutouts on left edge: 1.00wx1.00h, 1.18 and 13.34 inches from bottom and a circular cutout, 2.00 in diam, thru, centered 5.36 from left edge and 10.86 from bottom; near side is tapered 0.38 along top edge and has grooves, 2.00wx0.75d along left edge, 1.26wx0.50d along right edge and 2.40wx1.40d along top edge and has markings "up" and "aft" on 2 lines centered under top groove and part number to the right

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d