

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0620>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

16.340 inches

**Thickness:**

4.000 inches

**Length:**

22.320 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with 2 cutouts on right/short edge: 1.25wx1.50h, 1.74 inches from bottom and 1.26wx1.00h, 13.14 from bottom, 3 cutouts on left edge: 1.00wx1.00h, 1.28 and 7.06 and 13.76 inches from bottom, and a cutout, 7.50wx7.90h, 4.38 from top left corner (bottom left corner of this cutout is rounded with radius of 1.00 inch and bottom right corner with radius of 1.75); near side is tapered 0.50 along bottom edge and has groove, 2.40wx1.30d, 1.00 from top surface and has markings: "up aft" in top groove and part number below it

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T258-d