

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0628>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.090 inches

Thickness:

2.500 inches

Length:

23.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 3 cutouts on right/short edge: 1.00wx1.00h, 1.20 and 7.60 and 12.80 inches from bottom edge, 2 cutouts on left edge: 2.00wx2.50h at bottom corner and 1.25wx1.12h, 12.25 from bottom edge, and a cutout from top edge, 6.50wx4.69h, 7.32 from right edge; near side has 2 crosswise grooves: 1.25w, 12.52 from right edge and 1.00w, 7.32 from right edge; far side has markings: "up" and "aft" on 2 lines near upper right corner (far side up) and part number near opposite edge between bottom cutout/notch and next one up

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d