

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0633>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.660 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 3 cutouts on right/short edge: 1.25wx1.40h, 1.40 and 7.80 inches from bottom and 1.00wx1.40h, 18.40 from bottom, 2 cutouts on left edge, 1.26wx2.70h from bottom corner and 1.26wx3.66h from top corner, a cutout on top edge, 6.50wx6.06h, 8.75 from right edge; near side has taper of 0.76 along top edge; far side has grooves, 2.50wx2.25d along bottom edge, 2.356wx1.70d along top edge and has markings "up" and "aft" on 2 lines near upper left corner (far side up) and part number below top edge cutout

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d