

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0634>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.200 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 3 cutouts on right/short edge: 1.00wx1.00h, 2.40 and 7.70 inches from bottom edge, and 1.00wx1.40h, 14.20 from bottom, 2 cutouts on left edge: 1.25wx1.00h, 2.20 from bottom and 1.25wx3.50h at top corner, and a cutout on top edge, 3.40wx5.30h, 11.00 from right edge; near side is tapered 0.40 along top edge; far side has lengthwise grooves, 2.50wx1.80d along top edge and 2.40wx2.00d along bottom edge and a triangular cutout 1.25w on left edge (far side up) slanting from top surface, 13.70 inches from bottom edge to opposite surface, 8.40 from bottom and has markings "up" and "aft" near upper right corner (far side up) and part number centered above lower groove

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d