

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0642>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

17.760 inches

**Thickness:**

2.500 inches

**Length:**

21.070 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with 3 cutouts on right/short edge: 1.00wx1.00h, 1.40 & 7.50 & 14.80 inches up from bottom edge, a cutout on left edge, 5.00wx4.00h at bottom corner and a cutout on top edge 3.20wx6.76h, 12.50 from right edge; near side is tapered 0.30 along top edge; far side has groove 2.36wx0.60d along top edge and has cutout 1.25d, starting on left side, 3.20 above cutout, going to right 4.00 inches then perpendicularly up 3.00 inches and right to cutout

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T258-d