

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0642>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.760 inches

Thickness:

2.500 inches

Length:

21.070 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 3 cutouts on right/short edge: 1.00wx1.00h, 1.40 & 7.50 & 14.80 inches up from bottom edge, a cutout on left edge, 5.00wx4.00h at bottom corner and a cutout on top edge 3.20wx6.76h, 12.50 from right edge; near side is tapered 0.30 along top edge; far side has groove 2.36wx0.60d along top edge and has cutout 1.25d, starting on left side, 3.20 above cutout, going to right 4.00 inches then perpendicularly up 3.00 inches and right to cutout

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d