

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0644>

Fire Retarding Characteristic:

Not fire retarding

Width:

18.180 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: 1.00wx1.00h, 2.26 and 15.20 inches from bottom, a cutout 9.00wx7.00h from bottom left corner and an arched cutout from bottom edge, 8.00wx11.00h, 3.00 inches from right edge, a crosswise half-arch cutout from left edge, rounded side down, 3.90hx9.00w, 8.50 from bottom, and a cutout on left edge, 1.000wx1.00h, 2.58 from top; far side has a groove, 2.58wx0.84d along top edge and has markings: "up" in top groove and "aft" below it and part number to the right of "aft"

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d