

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0645>

Fire Retarding Characteristic:

Not fire retarding

Width:

18.000 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with cutouts on right/short edge: 1.00wx1.00h, 9.40 inchesd from bottom and 2.00wx2.50h from right top and bottom corners; a cutout on left edge, 1.26wx1.00h, 2.40 from bottom and one from left edge, 9.50wx3.50h, 8.40 from bottom and 2.00wx6.10h from left top corner; near side is tapered 0.30 along top edge; far side has lengthwise grooves, 2.40wx2.04d along bottom edge and 2.60wx0.75d along top edge and has markings "up" and "aft" on 2 lines near upper right corner (with far side up) and part number near upper left corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d