

View Online at <https://aerobasegroup.com/nsn/9330-01-502-0981>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.500 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 3 cutouts on right/short edge: 1.00wx1.00h, 2.0 & 8.50 & 15.15 inches from bottom; 2 cutouts on left edge: 1.26wx1.30h, 2.20 from bottom and 1.26wx1.00h, 14.40 from bottom; and rectangular cutout near center: 4.28wx3.50h, 7.65 from bottom and 8.56 from left edge with line cut through from top edge of cutout to top edge of item, 10.70 inches from left edge; far side is tapered 0.50 on bottom edge and has cutout, 9.10wx1.36hx0.88d, 6.40 from lefftedge (far side up) and has markings: "up" and "aft" near top left corner and part number centered 2.00 inches above bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d