

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1003>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.000 inches

Thickness:

2.500 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: 1.26wx1.00h, 1.90 & 8.20 inches from bottom; a cutout on bottom edge, 17.06wx1.16h, 2.80 from left edge; 2 cutouts on left edge: 1.26wx1.00h, 2.40 from bottom and 1.26wx0.90h at top left corner; and a cutout on top edge, 4.28w, 9.95 inches from left edge and ending in circle with radius 2.14, centered 9.34 from bottom; far side has crosswise grooves: with far side up: 2.00wx0.75d along left edge and 1.26wx1.30d along right edge and cutout, 1.75wx7.00lx0.75d, 4.50 from left edge and has markings: part number near upper right corner and "up" and "aft" below it

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d