

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1018>

Fire Retarding Characteristic:

Not fire retarding

Width:

14.600 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: 1.26wx3.00h, 1.80 inches from bottom, 1.26wx1.00h, 8.46 & 12.10 inches from bottom; 2 cutouts on left edge: 1.26wx2.80h, 2.70 from bottom and 1.26wx3.00h, 9.48 from bottom; near side has semicircular lengthwise groove, with radius 1.5 inches, 5.10 from bottom edge and groove, 2.20wx1.40d along top edge and has markings: "up fwd" near left edge below top groove and part number near bottom right corner; far side is tapered 0.56 along bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d