

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1051>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

15.380 inches

**Thickness:**

4.000 inches

**Length:**

21.070 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with 4 cutouts on right/short edge: 1.00wx1.60h, 1.40 inches from bottom, 1.50wx1.00h, 4.20 & 9.00 inches from bottom and 1.00wx1.00h, 12.80 from bottom; a cutout on bottom edge: 8.50wx1.16hx0.94d, 6.64 from right edge; near side has circular lengthwise groove with 1.00 radius centered 15.38 from bottom edge and a groove, 2.30wx1.40d along top edge and has markings: part number near left edge below top groove and "up fwd" to the right of p/n; far side has circular lengthwise groove with radius of 1.50 centered 8.25 from top edge and groove 8.50wx1.16hx0.94d, 6.64 from notched edge

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d