

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1061>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.260 inches

Thickness:

2.500 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Drectangular with 5 cutouts on right/short edge: 1.00wx1.00h, 2.10 & 5.00& 9.60 & 13.70 inches from bottom edge; a cutout on bottom edge: 7.32wx1.16h, 2.96 from left edge; 2 cutouts on left edge: 1.25wx1.00h, 2.84 & 13.00 from bottom; and a rectangular cutout near center: 3.00wx2.00h, 9.00 from bottom and 4.36 from right edge with line cut through from top edge of cutout to top of item, 5.36 from right edge; near side has crosswise grooves: 1.25wx0.50d along left edge and 2.00wx1.50d along right edge and has markings: part number near upper left corner and "up" and "fwd" on w lines to right of part number; far side has semicircular lengthwise cutout with radius 1.00 centered 9.90 inches from bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d