

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1069>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.780 inches

Thickness:

3.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Urectangular with 2 cutouts on right/short edge: 1.00wx1.00h, 1.18 and 13.34 inches from bottom, 2 cutouts on left edge: 1.26wx1.00h, 1.94 & 15.78 inches from bottom, and a circular cutout near top right corner: 2.00 in diameter, centered 10.86 from bottom and 5.36 from right edge; far side has taper of 0.38 on bottom edge, lengthwise groove: 2.40wx1.40d along top edge and crosswise grooves: 1.25wx0.50d along left edge and 2.00wx0.75d along right edge; and markings: "up" and "aft"

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d