NSN 9330-01-502-1069

Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-502-1069

| Fire Retarding Characteristic: |
|--|
| Not fire retarding |
| Width: |
| 15.780 inches |
| Thickness: |
| 3.000 inches |
| Length: |
| 22.320 inches |
| End Application: |
| Aircraft, thunderbolt ii, a-10 |
| Surface Condition: |
| Rough |
| Density Rating: |
| 1.2 pounds per cubic foot |
| Compression Strength At 25 Pct Deflection: |
| 0.35 pounds per square inch |
| Product Name: |
| Filler foam |
| Special Features: |
| Urectangular with 2 cutouts on right/short edge: 1.00wx1.00h, 1.18 and 13.34 inches from bottom, 2 cutouts on left edge: 1.26wx1.00h, |
| 1.94 & 15.78 inches from bottom, and a circular cutout near top right corner: 2.00 in diameter, centered 10.86 from bottom and 5.36 from |
| right edge; far side has taper of 0.38 on bottom edge, lengthwise groove: 2.40wx1.40d along top edge and crosswise grooves: |
| 1.25wxo.50d along left edge and 2.00wx0.75d along right edge; and markings: "up" and "aft" |
| Material: |
| Plastic, polyurethane |
| Material: |
| Plastic polyurethane |
| Supplementary Features: |
| Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T258-d |
| |