

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1079>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.340 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 3 cutouts on right/short edge: 1.00wx1.00h, 1.28 & 7.06 & 13.78 inches from bottom edge; 2 cutouts on left edge: 1.26wx1.50h, 1.74 from bottom and 1.25wx1.00h, 13.14 from bottom and a cutout on top edge, 7.50wx7.40h, 4.38 inches from right edge with bottom corners rounded: with radii of 1.75 on left & 1.00 on right; and a groove, 2.40wx1.30d along top edge, 1.00 from far side surface; far side is tapered 0.50 on bottom edge and has markings: "up aft" near top right edge (with far side facing up) and part number below it

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d