

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1092>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.260 inches

Thickness:

2.500 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 4 cutouts on right/short edge: 1.00wx1.00h, 2.10 & 5.00 & 9.60 & 13.70 inches from bottom; a cutout on bottom edge: 11.76wx1.16h, 2.96 from left edge and 2 cutouts on left edge: 1.25wx1.00h, 2.84 and 13.00 from bottom; a rectangular cutout near upper right corner, 3.00wx2.00h, 9.40 from bottom and 4.36 from right edge with line cut through from top of cutout to top edge of item, 5.36 from right edge; near side has markings: p/n near upper left corner and "up" and "fwd" on 2 lines to the right of p/n; far side has semicircular lengthwise groove with radius of 1.00 centered 9.90 from bottom

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d