

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1103>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.400 inches

Thickness:

4.000 inches

Length:

21.070 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with cutout on top/long edge: 3.00wx2.30h, 3.14 inches from left edge; near side has lengthwise semicircular groove with radius of 1.00 centered 9.24 from bottom edge and ending 2.50 from left edge and has markings: "up fwd" near upper right corner and part number near lower left corner; far side has lengthwise semicircular groove with radius of 2.00 centered 7.19 from bottom edge and lengthwise groove, 2.75wx1.75d along bottom edge and rectangular cutout, 3.00wx1.60hx1.00d, 3.14 inches from left edge (adjacent to rectangular cut through item)

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d