

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1285>

Fire Retarding Characteristic:

Not fire retarding

Width:

14.700 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: 1.25wx3.00h, 3.76 and 9.50 inches from bottom edge; a cutout on left edge: 0.80wx5.78h, 3.75 from bottom; near side has a lengthwise semicircular groove with radius of 2.00 inches centered 6.64 inches from bottom and a crosswise semicircular groove with radius of 2.00 centered 4.64 from left edge and running from top edge into lengthwise semicircular groove; and a lengthwise groove, 2.20wx1.40d along top edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d